

2-BIT UNIDIRECTIONAL VOLTAGE-LEVEL TRANSLATOR

 Check for Samples: [SN74AVC2T244](#)


FEATURES

- Wide Operating V_{CC} Range of 0.9 V to 3.6 V
- Low Static-Power Consumption, 6- μ A Max I_{CC}
- Output Enable Feature Allows User to Disable Outputs to Reduce Power Consumption
- ± 24 -mA Output Drive at 3.0 V
- I_{off} Supports Partial Power-Down-Mode Operation
- Input Hysteresis Allows Slow Input Transition and Better Switching Noise Immunity at Input
- Maximum Data Rates
 - 380 Mbps (1.8-V to 3.3-V Translation)
 - 200 Mbps (<1.8-V to 3.3-V Translation)
 - 200 Mbps (Translate to 2.5 V or 1.8 V)
 - 150 Mbps (Translate to 1.5 V)
 - 100 Mbps (Translate to 1.2 V)

- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Protection Exceeds JESD 22
 - 5000-V Human-Body Model (A114-A)

APPLICATIONS

- Handset, Smartphone, Tablet, Server

**DQE/DQM PACKAGE
(TOP VIEW)**


DESCRIPTION/ORDERING INFORMATION

This 2-bit unidirectional translator uses two separate configurable power-supply rails. The A port is designed to track V_{CCA} . V_{CCA} accepts any supply voltage from 0.9 V to 3.6 V. The B port is designed to track V_{CCB} . V_{CCB} accepts any supply voltage from 0.9 V to 3.6 V. This allows for low-voltage translation between 0.9-V, 1.2-V, 1.5-V, 1.8-V, 2.5-V and 3.6-V voltage nodes. For the SN74AVC2T244, when the output-enable (\overline{OE}) input is high, all outputs are placed in the high-impedance state. The SN74AVC2T244 is designed so that the \overline{OE} input circuit is referenced to V_{CCA} . This device is fully specified for partial-power-down applications using I_{off} . The I_{off} circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

ORDERING INFORMATION⁽¹⁾

T_A	PACKAGE ⁽²⁾	ORDERABLE PART NUMBER	TOP-SIDE MARKING
-40°C to 85°C	DQE – MicroQFN	SN74AVC2T244DQER	VA
	DQM – MicroQFN	SN74AVC2T244DQMR	VAH

(1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.

(2) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

DEVICE INFORMATION

PIN DESCRIPTION

PIN	FUNCTION
VCCA	Input Port DC Power Supply
VCCB	Output Port DC Power Supply
GND	Ground
An	Input Port
Bn	Output Port
OE	Output Enable

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
Voltage	DC Supply voltage, V_{CCA} , V_{CCB}	-0.5	4.6	V
	DC Input voltage, V_I	A_n -0.5	4.6	V
	Control Input, V_C	\overline{OE} -0.5	4.6	V
	DC Output voltage, V_O , $V_{CCA} = V_{CCB} = 0$	(Power Down) B_n -0.5	4.6	V
		(Active Mode) B_n -0.5	4.6	
	3-State Mode B_n -0.5	4.6		
	DC Input Diode current, I_{IK}	$V_I < GND$	-20	mA
	DC Output Diode current, I_{OK}	$V_O < GND$	-50	mA
	DC Output Source/Sink current, I_O		±50	mA
	DC Supply current per supply pin, I_{CCA} , I_{CCB}		±100	mA
I_{GND}	DC Ground current per ground pin		±100	mA
T_{stg}	Storage temperature range	-65	150	°C

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING CONDITIONS

		MIN	MAX	UNIT	
V_{CCA} , V_{CCB}	Positive DC Supply voltage	0.9	3.6	V	
V_I	Bus input voltage	GND	3.6	V	
V_I	Input voltage	GND	3.6	V	
V_C	Control input	\overline{OE} GND	3.6	V	
V_O	Bus output voltage	(Power Down Mode) B_n	GND	3.6	V
		(Active Mode) B_n	GND	V_{CCB}	V
		3-State Mode B_n	GND	3.6	V
T_A	Operating free-air temperature	-40	85	°C	
$\Delta t/\Delta v$	Input transition rise or fall rate V_I from 30% to 70% of V_{CC} ; $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0	10	nS	

ELECTRICAL CHARACTERISTICS^{(1) (2)}

over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS	V _{CCA} (V)	V _{CCB} (V)	–40°C to 85°C		UNIT
					MIN	MAX	
V _{IH}	Input HIGH Voltage (A _n , \overline{OE})		2.7 – 3.6	0.9 – 3.6	2.0	–	V
			2.3 – 2.7		1.6	–	
			1.4 – 2.3		0.65 × V _{CCA}	–	
			0.9 – 1.4		0.9 × V _{CCA}	–	
V _{IL}	Input LOW voltage (A _n , \overline{OE})		2.7 – 3.6	0.9 – 3.6	–	0.8	V
			2.3 – 2.7		–	0.7	
			1.4 – 2.3		–	0.35 × V _{CCA}	
			0.9 – 1.5		–	0.1 × V _{CCA}	
V _{OH}	Output HIGH voltage	I _{OH} = –100 μA; V _I = V _H	0.9 – 3.6	0.9 – 3.6	V _{CCB} – 0.2	–	V
		I _{OH} = –0.5 mA; V _I = V _H	0.9	0.9	0.75 × V _{CCB}	–	
		I _{OH} = –2 mA; V _I = V _H	1.4	1.4	1.05	–	
		I _{OH} = –6 mA; V _I = V _H	1.65	1.65	1.25	–	
		I _{OH} = –12 mA; V _I = V _H	2.3	2.3	2.0	–	
		I _{OH} = –12 mA; V _I = V _H	2.3	2.3	1.8	–	
		I _{OH} = –12 mA; V _I = V _H	2.7	2.7	2.2	–	
		I _{OH} = –18 mA; V _I = V _H	2.3	2.3	1.7	–	
V _{OL}	Output LOW voltage	I _{OH} = –24 mA; V _I = V _H	3.0	3.0	2.4	–	V
		I _{OH} = 100 μA; V _I = V _H	0.9 – 3.6	0.9 – 3.6	–	0.2	
		I _{OH} = 0.5 mA; V _I = V _H	1.1	1.1	–	0.3	
		I _{OH} = 2 mA; V _I = V _H	1.4	1.4	–	0.35	
		I _{OH} = 6 mA; V _I = V _H	1.65	1.65	–	0.3	
		I _{OH} = 12 mA; V _I = V _H	2.3	2.3	–	0.4	
		I _{OH} = 12 mA; V _I = V _H	2.7	2.7	–	0.4	
		I _{OH} = 18 mA; V _I = V _H	2.3	2.3	–	0.6	
I _I	Input Leakage Current	V _I = V _{CCA} or GND	0.9 – 3.6	0.9 – 3.6	–1.0	1.5	μA
			0	0.9 – 3.6	–1.0	1.3	
I _{OFF}	Power-Off Leakage Current	$\overline{OE} = 0V$	0.9 – 3.6	0	–1.0	1.5	μA
			0	0.9 – 3.6	–1.0	1.5	
I _{CCA}	Quiescent Supply Current	V _I = V _{CCA} or GND; I _O = 0	0.9 – 3.6	0.9 – 3.6	–	3.0	μA
I _{CCB}	Quiescent Supply Current	V _I = V _{CCA} or GND; I _O = 0	0.9 – 3.6	0.9 – 3.6	–	3.0	μA
I _{CCA} + I _{CCB}	Quiescent Supply Current	V _I = V _{CCA} or GND; I _O = 0	0.9 – 3.6	0.9 – 3.6	–	6.0	μA
ΔI _{CCA}	Increase in I _{CC} per Input Voltage, Other inputs at V _{CCA} or GND	V _I = V _{CCA} – 0.3 V; V _I = V _{CCA} or GND	3.6	3.6	–	5.0	μA

 (1) V_{CCO} is the V_{CC} associated with the output port.

 (2) V_{CCI} is the V_{CC} associated with the input port.

ELECTRICAL CHARACTERISTICS^{(1) (2)} (continued)

over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS	V _{CCA} (V)	V _{CCB} (V)	–40°C to 85°C		UNIT
					MIN	MAX	
ΔI_{CCB}	Increase in I _{CC} per Input Voltage, Other inputs at V _{CCA} or GND	V _I = V _{CCA} – 0.3 V; V _I = V _{CCA} or GND	3.6	3.6	–	5.0	μA
I _{OZ}	I/O Tri-State Output Leakage Current	T _A = 25°C, $\overline{OE} = 0$ V	0.9 – 3.6	0.9 – 3.6	–1.0	1.0	μA

AC ELECTRICAL CHARACTERISTICS

over operating free-air temperature range (unless otherwise noted)

Symbol	Parameter	V _{CCA} (V)	V _{CCB} (V)	MIN	MAX	UNIT
t _{PLH} , t _{PHL}	Propagation Delay, A _n to B _n	0.9 – 3.6	0.9 – 3.6		20	nS
		1.2 – 3.6	1.2 – 3.6		7	
		1.8 – 3.6	1.8 – 3.6		3.5	
t _{PZH} , t _{PZL}	Output Enable, \overline{OE} to B _n	0.9 – 3.6	0.9 – 3.6		23	nS
		1.2 – 3.6	1.2 – 3.6		6.5	
		1.8 – 3.6	1.8 – 3.6		4.1	
t _{PHZ} , t _{PLZ}	Output Disable, \overline{OE} to B _n	0.9 – 3.6	0.9 – 3.6		17	nS
		1.2 – 3.6	1.2 – 3.6		7	
		1.8 – 3.6	1.8 – 3.6		4.3	
t _{OSHL} , t _{OSLH}	Output to Output Skew, Time	0.9 – 3.6	0.9 – 3.6		0.15	nS
		1.2 – 3.6	1.2 – 3.6		0.15	
		1.8 – 3.6	1.8 – 3.6		0.15	

Table 1. CAPACITANCE⁽¹⁾

Symbol	Parameter	Test Conditions	TYP ⁽²⁾	Unit
C _{IN}	Control Pin Input Capacitance	V _{CCA} = V _{CCB} = 3.3 V, V _I = 0 V or V _{CCA/B}	3.5	pF
C _{I/O}	I/O Pin Input capacitance	V _{CCA} = V _{CCB} = 3.3 V, V _I = 0 V or V _{CCA/B}	5.0	pF
C _{PD}	Power Dissipation Capacitance	V _{CCA} = V _{CCB} = 3.3 V, V _I = 0 V or V _{CCA/B} , f = 10 MHz	33	pF

- (1) C_{PD} is defined as the value of the IC's equivalent capacitance from which the operating current can be calculated from: I_{CC(operating)} ≈ C_{PD} × V_{CC} × f_{IN} × N_{SW} where I_{CC} = I_{CCA} + I_{CCB} and N_{SW} = total number of outputs switching.
- (2) Typical values are at TA = +25°C.

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/ Ball Finish	MSL Peak Temp ⁽³⁾	Samples (Requires Login)
SN74AVC2T244DQER	ACTIVE	X2SON	DQE	8	5000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
SN74AVC2T244DQMR	ACTIVE	X2SON	DQM	8	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION
REEL DIMENSIONS

TAPE DIMENSIONS


A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

TAPE AND REEL INFORMATION

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74AVC2T244DQER	X2SON	DQE	8	5000	180.0	8.4	1.17	1.67	0.73	4.0	8.0	Q1
SN74AVC2T244DQMR	X2SON	DQM	8	3000	180.0	8.4	1.57	2.21	0.59	4.0	8.0	Q1


TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74AVC2T244DQER	X2SON	DQE	8	5000	202.0	201.0	28.0
SN74AVC2T244DQMR	X2SON	DQM	8	3000	202.0	201.0	28.0

DQE (R-PX2SON-N8)

PLASTIC SMALL OUTLINE NO-LEAD




4209779/B 10/2008

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. SON (Small Outline No-Lead) package configuration.
 - D. This package complies to JEDEC MO-287 variation X2EAF.

DQE (R-PX2SON-N8)

PLASTIC SMALL OUTLINE NO-LEAD



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. Customers should contact their board fabrication site for minimum solder mask web tolerances between signal pads. If 2 mil solder mask is outside PCB vendor capability, it is advised to omit solder mask.
 - E. Maximum stencil thickness 0,1016 mm (4 mils). All linear dimensions are in millimeters.
 - F. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
 - G. Over-printing land for acceptable area ratio is not viable due to land width and bridging potential. Customer may further reduce side aperture dimensions if stencil manufacturing process allows for sufficient release at smaller opening.
 - H. Suggest stencils cut with lasers such as Fiber Laser that produce the greatest positional accuracy.
 - I. Component placement force should be minimized to prevent excessive paste block deformation.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Mobile Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2012, Texas Instruments Incorporated