

## Extruded heatsinks for PCB mounting

for semiconductor screw-mounting

	<p>... STS</p>	<p>... STIS</p>	<p>... STSB</p>
<b>art. no.</b>	<b>↔ [mm]</b>	<b>R<sub>th</sub> [K/W]</b>	<b>⊕</b>
<b>SK 104 25,4 ...</b>	25.4	14	TO 220/ SOT 32/ TO 3 P
<b>SK 104 38,1 ...</b>	38.1	11	TO 220/ SOT 32/ TO 3 P
<b>SK 104 50,8 ...</b>	50.8	9	TO 220/ SOT 32/ TO 3 P
<b>SK 104 63,5 ...</b>	63.5	8	TO 220/ SOT 32/ TO 3 P
<b>please indicate:</b>			
	... <b>mounting method</b>		
	<b>STS</b> =with solder pin		
	<b>STIS</b> =with solder pins and insulating washer		
	<b>STSB</b> =with threaded bolt M 3, brass		

E = mounting method

special lengths and transistor drillings on request

**surface treatment:** black anodised

horizontal for semiconductor screw-mounting

<b>art. no.</b>	<b>↔ [mm]</b>	<b>R<sub>th</sub> [K/W]</b>	<b>⊕</b>
<b>SK 104 25,4 LS</b>	25.4	14	TO 220/ SOT 32/ TO 3 P
<b>SK 104 38,1 LS</b>	38.1	11	TO 220/ SOT 32/ TO 3 P
<b>SK 104 50,8 LS</b>	50.8	9	TO 220/ SOT 32/ TO 3 P
<b>SK 104 63,5 LS</b>	63.5	8	TO 220/ SOT 32/ TO 3 P

special lengths and transistor drillings on request

**surface treatment:** black anodised